



INTERLOCKING SHAFT KNOB TO BRIDGE GAP AND ALLOW DOCKING OF THE PROBE TO THE SHAFT

SPECIFICATIONS

CAPACITY: 500 POUNDS
 MAX. FACE WIDTH: 7-9"
 MAX. DIAMETER: $\phi 52$ "

APPROVAL

Approved
 As Noted
 Revise and Resubmitt
 By: _____ Date: _____

TOLERANCES UNLESS SPECIFIED		REV		DATE	BY	CHANGES
MACHINED .XXX	- .005"					
.XXX	- .01"					
X	- .05"					
FRACTIONS	- $\pm 1/16$ "					
ANGULAR	- $\pm 3^\circ$					
<small>NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION: TILT-LOCK CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED THEREON. THIS DRAWING AND/OR TECHNICAL INFORMATION IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN OR REFERRED TO HEREON WITHOUT DIRECT WRITTEN PERMISSION FROM TILT-LOCK TO THE USER.</small>						
DRAWN BY:	TGK	DATE:	3/14/06	SCALE:	NONE	WEIGHT:
RELEASED BY:	GLM	DWG:	TA63019			
<small>TILT-LOCK IS NOT RESPONSIBLE FOR THE STRENGTH OF BUILDING MEMBERS FURNISHED BY OTHERS.</small>						<small>REVISIONS</small> X D



TITLE: ROLL LIFTING BEAM ASSEMBLY
 $\phi 52$ " X 9" WIDE X 500 LBS.