



INTERLOCKING SHAFT KNOB TO BRIDGE GAP AND ALLOW DOCKING OF THE PROBE TO THE SHAFT

SPECIFICATIONS

CAPACITY: 500 POUNDS
 MAX. FACE WIDTH: 7-9"
 MAX. DIAMETER: Ø52"

APPROVAL

Approved
 As Noted
 Revise and Resubmitt
 By: _____ Date: _____

TOLERANCES UNLESS SPECIFIED		REV. DATE BY CHANGES	
MACHINED .XXX	- .005"		
.XXX	- .01"		
X	- .05"		
FRACTIONS	- ±1/16"		
ANGULAR	- ±3°		
NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION: TILT-LOCK CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED THEREON. THIS DRAWING AND/OR TECHNICAL INFORMATION IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN OR REFERRED TO HEREON WITHOUT DIRECT WRITTEN PERMISSION FROM TILT-LOCK TO THE USER.		DRAWN BY: TKG	DATE: 3/14/06
TILT-LOCK IS NOT RESPONSIBLE FOR THE STRENGTH OF BUILDING MEMBERS FURNISHED BY OTHERS.		RELEASED BY: GLM	DWG: TA63019
TITLE: ROLL LIFTING BEAM ASSEMBLY Ø52" X 9" WIDE X 500 LBS.		SCALE: NONE	WEIGHT: X
		SIZE: D	REV: 1

